



TECHNICAL DATA SHEET

rev. 00 of 21st January, 2010

DILUENTE GRIP (retarder)

code SO1210

TECHNICAL DATA

(based on room temperature of +23°C and 65% of relative air humidity)

Appearance	clear liquid
Colour	transparent
Addition ratio	1 - 5 %
Viscosity	11" F4 ± 2" F4
Specific weight	1.04 ± 0.01
VOC (volatile organic compounds)	50.0% ± 0.5 %

DESCRIPTION

A retarding thinner that improves the penetration and adhesion of water-based primers and finishes on difficult supports.

This product is compatible with all our water-based finishes and primers.

PACKAGING

5 and 10 litre plastic cans
2.5, 1 and 0.2 litre plastic bottles

DIRECTIONS

Pour DILUENTE GRIP into the primer/finish and mix thoroughly until fully dissolved. Wait 10 - 15 minutes, then apply.

NOTICE

- This product is not compatible with solvent-based systems.
- Too much DILUENTE GRIP greatly reduces the viscosity of the product and greatly increases its drying times

Protect from freezing!

Dispose of excess product and empty containers properly.

If the original unopened container is stored in a cool and dry place, the product will keep for at least 12 months.

N.B. The information contained in this technical data sheet is to the best of our knowledge and experience. Since the conditions of use are beyond our control, no warranty is given or implied.